

Blue Box

Digital Vessel Recording System

Blue Box is a hardened Digital audio/video recording system that is capable of capturing Radar, Charts, Camera Video, AIS, VHF Audio and other optional sources continuously.

The system can be connected to your vessel network for remote viewing/listening, downloading of recorded data and system setup changes. Blue Box can also alarm letting you know when there is a problem.

Solid State Drives, HDMI and ESATA outputs are some of the latest features. Blue Box also has an onboard USB for local backup.



- Radar Video
- VHF Communications
- Analog Video
- IP Video
- Vessel Network
- 28 Days Backup
- RAID Setup Options
- 8 or 16 Channel Systems

Blue Box Specifications

System	Main Processor Operating System System Resources Control Mode	High performance embedded microprocessor Embedded LINUX Pentaplex function: live, recording, playback, backup & remote access Front panel, USB mouse, IR remote control, Keyboard, Network
Video	Input Standard Output	8 or 16 channel, BNC(1.0Vp-p, 75Ω) NTSC(525Line, 60f/s), PAL(625Line, 50f/s) BNC, VGA or HDMI
Audio	Input Output	4 channel, Solid State VHF Audio Module Channel 1 for bidirectional-talk input synchronously 1 channel, BNC(200-3000mV, 5KΩ)
Display	Display Split Resolution Tour Display Privacy Masking OSD	1/4/8/9 1280×1024, 1280×720, 1024×768, 800×600, 1366×768 Support 4 self-defined four-sided zones for privacy masking for each camera Camera title, time, video loss, camera lock, motion detection, recording
Recording/ Backup	Compression Image Resolution Backup	H.264 / G.711 QCIF, CIF, 2CIF, D1, HD1, HD960 Channel 2~8: CIF/QCIF (1~25/30fps), D1 (1~6/7fps) Extra Stream: QCIF(1~25/30fps), CIF (1~6/7fps) Flash drive/ USB HDD/ Network download
Network Hard Disk eSATA USB RS232 RS485	Ethernet Functions Remote Operation eSATA External Storage HDD Management Interface Interface Interface	RJ-45 port (10/100M) TCP/IP, UDP, DHCP, DNS, DDNS IP Filter, DDNS, FTP, SNMP Trap, Email, Alarm Server Monitor, PTZ control, Playback, System setting, File download, Log information Single drive or RAID1 Mirrored Setups are available eSATA external storage Hard disk hibernation technology, HDD faulty alarm 2 ports, 1 for mouse control, 1 for backup Keyboard, PC communication PTZ control
Power	Power Supply Consumption Environment Dimension Weight	AC 100~240 V, 50/60 Hz 35W with Cooling Fans Running (-10+55°C) / 10~90%RH / 86~106kpa 17.56 x 18.13 x 7.88 15LBS (without HDD)